

# PRO-SPRAY™

Meet the strongest, most versatile sprinkler body in the industry.

## KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

## ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades

## OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 3 m of elevation)
- Reclaimed water ID cap

## USER-INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



### Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps.

## PRO-SPRAY - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
<b>PROS-00</b> = Shrub adapter	<b>(blank)</b> = No option
<b>PROS-02</b> = 5 cm pop-up	<b>CV</b> = Factory-installed drain check valve (Pop-up models only)
<b>PROS-03</b> = 7.5 cm pop-up	<b>R</b> = Factory-installed reclaimed body cap (shrub moulded in purple)
<b>PROS-04</b> = 10 cm pop-up	
<b>PROS-06</b> = 15 cm pop-up (no side inlet)	
<b>PROS-12</b> = 30 cm pop-up (no side inlet)	

## PRO-SPRAY (SIDE INLET) MODELS

- PROS-06-SI** = 15 cm pop-up with side inlet
- PROS-12-SI** = 30 cm pop-up with side inlet

### Examples:

- PROS-06-CV** = 15 cm pop-up, drain check valve
- PROS-12-CV-R** = 30 cm pop-up, drain check valve, reclaimed body cap



### PROS-00

Retracted height: 4 cm  
Inlet size: ½"



### PROS-02

Retracted height: 10 cm  
Pop-up height: 5 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



### PROS-03

Retracted height: 12.5 cm  
Pop-up height: 7.5 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



### PROS-04

Retracted height: 15.5 cm  
Pop-up height: 10 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



### [A] PROS-06-SI

[B] **PROS-06**  
Retracted height: 22.5 cm  
Pop-up height: 15 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



### [A] PROS-12-SI

[B] **PROS-12**  
Retracted height: 41 cm  
Pop-up height: 30 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"